



SHOCKER PINTLE HOOK - CHANNEL MOUNT

SKU: SH-331 (3.68" ID W/ 5/8" PIN HOLES)

INSTALLATION

-Install onto Shocker Hitch unit and secure with 5/8" pins, this pintle hook channel mount is designed for Shocker Air series, Impact cushion series, and XR series.

-IMPORTANT: The Shocker Pintle Hook - Channel Mount is NOT designed to flip, please see Figure 1 and Figure 2 for your reference.

OPERATING THE PINTLE HOOK

-Open latch by removing the safety pin then pull the lever upward, please see Figure 3 and Figure 4.

-Position lennette pintle ring over the "horn" over the pintle hook and lower into place, push latch closed and insert safety pin.

ADDITIONAL INFORMATION

-Pintle Hook Weight Rating - 2,000 lbs. MAX vertical load / 20,000 lbs. MAX trailer weight

-Rise and Drop Ranges

-Air hitches - 1/2" to 4-1/2" drop

-Cushion hitches - 4" rise to 4" drop

-XR hitches - 4" rise to 4" (8-hole) or 5-1/2" rise to 5-1/2" drop (10-hole)

SAFETY NOTICES

-Towing capacity is limited by the lowest rated component. It is imperative that you always read and follow the tongue and towing weight recommendations of the truck, receiver, hitch, ball, coupler and trailer you are towing.



Figure 1: Install pintle hook with the lever facing upward



Figure 2: DO NOT install pintle hook "upside down"



Figure 3: Pull safety pin from pintle hook latch lever



Figure 4: Pulling upward on the lever, open the pintle hook horn.

THANK YOU FOR CHOOSING SHOCKER HITCH

Shocker Hitch: Safer Smoother Towing - 2804 3RD AVE SW, JAMESTOWN ND, 58401 - (701)-707-2666

-Email: service@shockerhitch.com -Website: www.shockerhitch.com -Installation Videos on Shocker Hitch YouTube Channel