



SHOCKER RAISED CHANNEL PINTLE HOOK - SH-335

Towing Capacity 10-Tons (20,000 lbs. GTW)

-INSTALLATION

- Start by attaching it to Shocker Hitch to desired height and secure with pins.
- Open the pintle hook by removing the safety pin and lifting up on the handle (see Figures 1 & 2).
- Drop trailer with pintle ring onto open pintle hook.
- Close the pintle by pushing the latch down until it is locked into place (see Figure 3).
- Secure pintle hook by reinserting the safety pin (see Figure 4).

-SAFETY NOTICE

- Towing capacity is limited by the lowest rated component. It is imperative that you always read and follow the tongue and towing weight recommendations of the truck, receiver, hitch, ball, coupler and trailer you are towing.
- NEVER** run the pintle hook upside down.



Figure 1: Pull on lever to release latch



Figure 2: Pull up on latch to open pintle hook



Figure 3: Drop trailer with pintle ring onto pintle hook and push latch down firmly



Figure 3: Reinsert safety pin

THANK YOU FOR CHOOSING SHOCKER HITCH

Shocker Hitch: Safer Smoother Towing - 2801 3RD AVE SW, JAMESTOWN ND, 58401 - (701)-707-2666

•Email: service@shockerhitch.com •Website: www.shockerhitch.com •Installation Videos on [Shocker Hitch](#) YouTube Channel